






Nitroxtec Heated Type Desiccant Dryer



NDDB-180

m ³ / minute	180,00
m ³ / hour	10800
Operating pressure [bar] (g)	13
Inlet - Outlet	DN200 FLANGE - DN200 FLANGE
Purge air loss	0 – 3% (adjustable)
Dimensions L x W x H [mm]	2200 x 2800 x 2600
Shipping dimensions L x W x H [mm]	2250 x 2850 x 2740
Maintenance area L x W x H [mm]	2700 x 3300 x 3100
Raw Material	High-Efficiency Silica Gel
Raw Material Weight [kg]	3195
Net Weight [kg]	6000
Gross Weight [kg]	6050
Power	380-400V AC 50/60 Hz 78 KW
FLANGE Filters [µm]	Pre-filter 0,1 - Post-filter 0,01
Operating temperature	5-45°C
Minimum inlet pressure	4,5 bar (g)
Dew point	-40°C
Air quality ISO Specification	ISO 8573.1:2010.1.4.1

Pressure Correction Factor									
Pressure (bar g)	5,00	6,00	7,00	8,00	9,00	10,00	11,00	12,00	13,00
Factor	0,75	0,88	1,00	1,12	1,25	1,37	1,48	1,58	1,66

Temperature Correction Factor						
Temp (°C)	20,00	25,00	30,00	35,00	40,00	45,00
Factor	1,00	1,00	1,00	1,00	0.8	0.73