






Nitroxtec High-Pressure Desiccant Dryer



NDD- 1.2/50BAR

m ³ / minute	1,2
m ³ / hour	72
Operating pressure [bar] (g)	40
Inlet - Outlet	DN15/BSP 1/2" Female - DN15/BSP 1/2" Female
Purge air loss	5%
Dimensions L x W x H [mm]	390 × 440 × 1020
Shipping dimensions L x W x H [mm]	440 × 490 × 1140
Maintenance area L x W x H [mm]	890 × 940 × 1520
Raw Material	Activated Alumina
Raw Material Weight [kg]	8
Net Weight [kg]	54
Gross Weight [kg]	65
Power	110-240V AC 50/60 Hz 50 W
Pre-filter - Post-filter [µm]	0,1 - 0,01
Operating temperature	5-45°C
Minimum inlet pressure	4,5 bar (g)
Maximum inlet pressure	16 bar (g)
Dew point	-40°C
Air quality ISO Specification	ISO 8573-1:2010 [Class 1 : Class 2] (Particles : Humidity)

Compressed Air Inlet Temperature (Ti)

Temp (°C)	25,00	30,00	35,00	40,00	45,00	50,00
Ki	1,00	1,00	1,00	0,96	0,90	0,83

Deviating working pressure P at the dryer inlet

P bar(g)	20,00	25,00	30,00	35,00	40,00	50,00
Kp	0,50	0,63	0,75	0,88	1,00	1,25