




Nitroxtec Activated Carbon Tower Filtrir



NCT-36

m ³ / minute	16,67
m ³ / hour	2200
Operating pressure [bar] (g)	10
Inlet - Outlet	DN80/BSP 3" Female - DN80/BSP 3" Female
Dimensions L x W x H [mm]	700 x 700 x 2250
Shipping dimensions L x W x H [mm]	750 x 2300 x 750
Maintenance area L x W x H [mm]	1200 x 1200 x 2750
Residual oil vapour content nominal (mg/m3)	< 0.003
Raw Material	Activated Carbon
Raw Material Weight [kg]	210
Net Weight [kg]	440
Gross Weight [kg]	480
Pre-filter - Post-filter [µm]	0,1 - 0,01
Operating temperature	5-45°C
Minimum inlet pressure	4,5 bar (g)
Maximum inlet pressure	10 bar (g)
Dew point max	+3°C
Air quality ISO Specification	ISO 8573-1:2010 [Class 1 : Class 1] (Particles : Oil)

Compressed Air Inlet Temperature (Ti)						
Temp (°C)	25,00	30,00	35,00	40,00	45,00	50,00
Ki	1,00	1,00	1,00	0,96	0,90	0,83

Deviating working pressure P at the dryer inlet												
P bar(g)	5,00	6,00	7,00	8,00	9,00	10,00	11,00	12,00	13,00	14,00	15,00	16,00
Kp	0,75	0,88	1,00	1,06	1,12	1,17	1,22	1,27	1,32	1,37	1,41	1,46

NITROXTEC ENDÜSTRİYEL MAKİNA

Address: İkitelli O.S.B. Dersan Blok Sokak Trios 2023 B Blok No:73 Başakşehir - İstanbul Türkiye

Phone: +90 212 544 42 61 **Email:** info@nitroxtec.com